```
3/4/1
DIALOG(R) File 351: Derwent WPI
(c) 2004 Thomson Derwent. All rts. reserv.
AA- 1991-243479/ 199133 |
DX- <RELATED> 1999-565564
XR- <XRAM> C91-105772
XR- <XRPX> N91-185689
TI- Laminated film used as base film for magnetic tape - prepd. by
    laminating e.g. unstretched thermoplastic resin film with
    fluorine-contg. polymer film and heat treating
PA- TOYOBO KK (TOYM )
NC- 001
NP- 002
PN- JP 3159739
                 A 19910709 JP 89300388
                                             A 19891117 199133 B
                 B2 20000404 JP 89300388
PN- JP 3028537
                                             A 19891117 200022
AN- <LOCAL> JP 89300388 A 19891117; JP 89300388 A 19891117
AN- <PR> JP 89300388 A 19891117
FD- JP 3159739
                 Α
FD- JP 3028537
                 B2 B32B-027/30
                                   Previous Publ. patent JP 3159739
LA- JP 3159739(6); JP 3028537(9)
AB- <BASIC> JP 3159739 A
        Laminated film is prepd. by laminating unstretched or monoaxially
    stretched thermoplastic resin film with film comprising mainly F-contg.
    polymer; monoaxially or biaxially stretching the laminated film; and
    heat-treating the stretched film.
         The base film is pref. of polyester, polyamide, polycarbonate or
    cellulose. The F-contg. polymer is pref. prepd. by (co)polymerising an
    ethylenically unsatd. monomer contg. a perfluoroalkyl gp., e.g. of
    formula CnF2n+1CH2O(CO)-C(R1)=CH2 or CnF2n+1CH2CH=CH2 where R1, R2 are
    each H or a lower alkyl solely or in combination with a copolymerisable
    monomer (e.g., ethylenically unsatd. carboxylate ester of
    polyoxyalkylene glycol, glycidyl methacrylate, hydroxyalkyl acrylate,
    methacrylic acid, acrylamide, acrylate ester, acrylonitrile, vinyl
    acetate or methylvinyl ether). The F-contg. (co)polymer is laminated on
    the base film by coating or dipping its emulsion or soln. or by
    coextrusion or extrusion lamination.
         USE/ADVANTAGE - The film has water-repellency, oil-repellency,
    antifouling activity, nontackiness, releasability, protection of
    substrate and high moisture resistance. It is used as base film for
    magnetic tape, insulating tape, photographic film, tracing film and
    packing film for foods.
        Dwg.0/0|
DE- <TITLE TERMS> LAMINATE; FILM; BASE; FILM; MAGNETIC; TAPE; PREPARATION;
    LAMINATE; UNSTRETCHED; THERMOPLASTIC; RESIN; FILM; FLUORINE; CONTAIN;
    POLYMER; FILM; HEAT; TREAT
DC- A14; A32; P73
IC- <MAIN> B32B-027/30
IC- <ADDITIONAL> B32B-007/02; B32B-027/08
MC- <CPI> A04-E10; A11-B02A; A11-B02C; A12-S06B; A12-S06C1
```

FS- CPI; EnqPI |